



INTERCOLOR MATT EMULSION

SCOPE

Intercolor matt emulsion is a high quality water based paint with 100% styrene acrylic emulsion that dries rapidly & give the walls freshly painted look year after year. It is enriched with antifungal properties & gives the walls a rich matt finish. It is good for disguising small imperfection that appears on the wall.

It is characterized by excellent flow and levelling, opacity and smooth finish.

PRODUCT INFORMATION

Product code	: IME
Pack size	: 20 ltr, 4ltr
Shade / Color range	: Selected colors from INTERCOLOR Color charts Customized colors available
Composition Nominal	: Styrene-acrylic copolymer emulsion
Application tools	: Roller, Brush

TECHNICAL INFORMATION / DATA

Specific gravity	: 1.55 ± 0.04
% NVM (by wt.)	: 68 ± 2
Viscosity of supply	: 110 – 125 Ku on stormer viscometer at 30°C
Thinner	: Municipal / Potable water
Thinning ratio (by vol.)	: Rolling – as such or upto 5% if required. Brushing – 12 - 16 %
Covering capacity	: 3.8 – 5 sq.mt / litre by Roller. Practical coverage may depend on surface Profile & method of application.

Drying time at 30°C

Touch Dry	: 15 min.
Hard dry / Recoat ability	: 90 – 120 min.

AREAS OF APPLICATION

Suitable for interior and exterior use on plaster/concrete, fibrous cement sheeting, stucco/roughcast, concrete blocks, brick work, timber and weather boards.

SURFACE PREPARATION

Remove dust, dirt, grease, and loose flaking paint by sanding with suitable abrasive paper and thoroughly cleaning the surface. If mould or fungus is present on the concrete wall then treat with anti-fungus solution.

APPLICATION

Stir the contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Apply uniformly by convenient method of application, after thinning the paint to obtain the desired level of consistency. 2nd coat to be applied only after 80 – 120 min of the 1st coat.

FLAMMABILITY & TRANSPORT INFORMATION

Non-flammable

SAFETY INFORMATION AND PRECAUTION

- Do not apply at temperature below 10°C
- Provide adequate ventilation during use
- Keep out of reach of children
- Avoid contact with skin and eyes, wear suitable protective clothing such as overalls, goggles, dust masks and gloves
- Check cross adhesion of old paint before repainting

