



INTERGLOSS ENAMEL

RECOMMENDED USE : AS A TOPCOAT FOR EXTERIOR AND INTERIOR USE ON STEEL STRUCTURES, WOOD, METAL, CHIPBOARD AND CONCRETE.

COLORS : WHITE, BLACK AND AS PER SELECTED COLOR IN COLOR CARD.

SOLIDS : 55% BY VOLUME

SPECIFIC GRAVITY : 1.07 \pm 0.05

VISCOSITY : 300 - 400 SEC AT @ 30°C

DRYING TIME : SURFACE DRY AT 4-6 HOURS AND HARD DRY AT 12 HOURS.

FLASH POINT : 32°C

AVAILABLE PACKAGE : 4 LITERS, 20 LITERS

SPREADING RATE : 8-10M²/LITER

SHELF LIFE : 2 YEARS

SURFACE PREPARATION : *THE SURFACE SHOULD BE THOROUGHLY CLEAN. DEPENDING ON THE SUBSTRATE, IN APPROPRIATE PRIMER AND UNDERCOAT SHOULD BE USED.*

APPLICATION DATA : *BRUSH, OIL ROLLER OR SPRAY.*

THINNING : *USE DPK SPIRIT OR PETROL FOR THINNING.*

HANDLING : *STIR WELL BEFORE USE. KEEP CONTAINERS TIGHTLY CLOSED.*