



INTERPUTTY GOLD

(Exterior use)

SCOPE

Interputty-Gold is a water based screeding material meant for filling, smoothing out cracks and dents on the walls. It provides a smooth surface for paint application.

It has Good water Resistant & it's especially for Exterior of the wall. Thinning if required can be done by adding water and blending to a smooth paste. It is characterized by excellent scrub resistant, opacity and smooth finish.

It also has excellent cutting & filling properties.

PRODUCT INFORMATION

Product code	: IPG
Pack size	: 28 kg
Shade / colour range	: White
Composition Nominal	: Styrene-acrylic copolymer emulsion
Application tools	: Putty knife/Putty trowel

TECHNICAL INFORMATION / DATA

Specific gravity	: 1.73 ± 0.03
% NVM (by wt.)	: 76 ± 1
Thinner	: Municipal / Potable water
Thinning ratio (by vol.)	: As such without dilution If required, water can be sprinkled

Drying time at 30 C

Touch Dry	: 30 min.
Hard dry / Recoatability	: 8 – 10 hrs

AREAS OF APPLICATION

Suitable for interior and exterior use on plaster/concrete, asbestos, concrete brick work, timber and false ceiling.

SURFACE PREPARATION

Remove dust, dirt, grease, and loose flaking paint by sanding with suitable abrasive paper and thoroughly cleaning the surface. If mould or fungus is present on the concrete wall then treat with anti-fungus solution.

Large cracks should be filled by mixing cement and sand in the ratio 1:3.

APPLICATION

Apply interputty Gold using putty applicator to obtain a smooth and uniform surface. After drying, sand with suitable Emery paper for smooth finish of the wall. Apply uniformly by convenient method of application, after thinning the paint to obtain the desired level of consistency. 2nd coat to be applied only after 8 - 10hrs of the 1st coat.

FLAMMABILITY & TRANSPORT INFORMATION

Non-flammable

SAFETY INFORMATION AND PRECAUTION

- Do not apply at temperature below 10°C
- Provide adequate ventilation during use
- Keep out of reach of children
- Avoid contact with skin and eyes, wear suitable protective clothing such as overalls, goggles, dust masks and gloves
- Check cross adhesion of old paint before Screeding
- Dispose in landfills only.