



INTERCOLOR QUALITY PAINTS

INTERSILK EMULSION

SCOPE

Intersilk is a premium emulsion paint formulated to provide a luxurious smooth finish to the walls. This is a high quality water based paint with best styrene acrylic emulsion that dries rapidly, imparts glossy nature and is washable to give the walls freshly painted look year after year. It has reduced dirt pick-up & gives the walls a rich finish. It is characterized by excellent flow and levelling, opacity and smooth finish.

It imparts high sheen appearance.

PRODUCT INFORMATION

Product code	: SKE
Pack size	: 4 ltr, 20 ltr
Shade / colour range	: As per INTERCOLOR colour charts. Customized colors available
Composition Nominal	: Styrene-acrylic copolymer emulsion
Application tools	: Roller, Brush

TECHNICAL INFORMATION / DATA

Specific gravity	: 1.20 ± 0.04
% NVM (by wt.)	: 48 ± 1
Viscosity of supply	: 90 – 100 Ku on stormer viscometer at 30°C
Thinner	: Municipal / Potable water
Thinning ratio (by vol.)	: Rolling – as such or upto 5% if required. Brushing – 10 - 15%
Covering capacity	: 5 - 6 sq.mt / litre by Roller Practical coverage may depend on surface Profile, method of application and weather conditions.
Drying time at 30°C	
Touch Dry	: 20 min.

Hard dry / Recoatability : 100 – 120 min.

AREAS OF APPLICATION

Suitable for interior and exterior use on plaster/concrete, fibrous cement sheeting, stucco/roughcast, concrete blocks, brick work, timber and weather boards.

SURFACE PREPARATION

Remove dust, dirt, grease, and loose flaking paint by sanding with suitable abrasive paper and thoroughly cleaning the surface. If mould or fungus is present on the concrete wall then treat with anti-fungus solution.

APPLICATION

Stir the contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Apply uniformly by convenient method of application, after thinning the paint to obtain the desired level of consistency. 2nd coat to be applied only after 100 – 120 min of the 1st coat.

FLAMMABILITY & TRANSPORT INFORMATION

Non-flammable

SAFETY INFORMATION AND PRECAUTION

- Do not apply at temperature below 10°C
- Provide adequate ventilation during use
- Keep out of reach of children
- Avoid contact with skin and eyes, wear suitable protective clothing such as overalls, goggles, dust masks and gloves
- Dispose in landfills only.