



INTERPEARL TEXTURED

(Interior)

SCOPE

Interpearl textured is a water based material meant for base coat or design coat for the decorative paints on the walls. It provides a textured surface for polish application. Thinning if required can be done by adding water and blending to a smooth paste. Highly recommended only for inside.

PRODUCT INFORMATION

Product code	: IPT
Pack size	: 28 kg
Shade / colour range	: White
Composition Nominal	: Styrene-acrylic copolymer emulsion
Application tools	: Textured roller

TECHNICAL INFORMATION / DATA

Specific gravity	: 1.75 ± 0.03
% NVM (by wt.)	: 70 ± 1
Thinner	: Municipal / Potable water
Thinning ratio (by vol.)	: As such or upto 1- 3% if required.
Drying time at 30 C	
Touch Dry	: 60 -90 min.
Hard dry / Recoatability	: 20 – 24 h

AREAS OF APPLICATION

Suitable only for interior use on plaster/concrete, asbestos & concrete brick work

SURFACE PREPARATION

Remove dust, dirt, grease, and loose flaking paint by sanding with suitable abrasive paper and thoroughly cleaning the surface. If mould or fungus is present on the concrete wall then treat with anti-fungus solution.

Large cracks should be filled by mixing cement and sand in the ratio 1:3

In case of virgin plastered wall, the wall should be primed with white paint before the application of IPT base

APPLICATION

Apply IPT using textured roller to obtain a required uniform thickness for rolling the design roller. After drying, apply 2 coats of polish to get your desired color.

After polish dries, apply HDG to perceive the glittering finish of the decorative paint

FLAMMABILITY & TRANSPORT INFORMATION

Non-flammable

SAFETY INFORMATION AND PRECAUTION

- Do not apply at temperature below 10°C
- Provide adequate ventilation during use
- Keep out of reach of children
- Avoid contact with skin and eyes, wear suitable protective clothing such as overalls, goggles, dust masks and gloves
- Check cross adhesion of old paint before the application of IPT base
- Dispose in landfills only.