

# **SHEEN COAT**

# **SCOPE**

Sheet coat is a translucent (Partial transparent) emulsion paint formulated to provide a luxurious color & smooth finish to the walls. This is a high quality water based paint that dries rapidly, imparts glossy nature & determine the final color of the wall.

It has reduced dirt pick-up & gives the wall a rich finish. It is characterized by excellent flow and levelling, moderate opacity and smooth finish.

# PRODUCT INFORMATION

Product code : SHN

Pack size : 4 ltr

**Shade / colour range** : As per IPT colour charts.

Customized colors available

**Composition Nominal** : Styrene-acrylic copolymer emulsion

**Method of Application** : Roller, Brush

# **TECHNICAL INFORMATION / DATA**

Specific gravity :  $1.04 \pm 0.02$ 

% NVM (by wt.) : 32 ± 1

**Viscosity of supply** : 80 – 85 KU on stormer viscometer at 30°c

**Thinner**: Municipal / Potable water

**Thinning ratio (by vol.)** : Rolling – without dilution

Brushing – 5% water, if required

**Covering capacity** : 2 - 3 sq.mt / litre by Roller

Practical coverage may depend on surface

Profile, method of application and weather

conditions.

#### Drying time at 30°C

Touch Dry : 30 min.

Hard dry / Recoatability : 120 – 140 min.

#### **AREAS OF APPLICATION**

Suitable for interior and exterior use on plaster/concrete, fibrous cement sheeting, stucco/roughcast, concrete blocks, brick work, timber and weather boards.

# **SURFACE PREPARATION**

Remove dust, dirt, grease, and loose flaking paint by sanding with suitable abrasive paper and thoroughly cleaning the surface. If mould or fungus is present on the concrete wall then treat with anti-fungus solution.

# **APPLICATION**

Stir the contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Apply uniformly by convenient method of application, after thinning the paint to obtain the desired level of consistency. 2<sup>nd</sup> coat to be applied only after 120 – 140 min of the 1<sup>st</sup> coat.

# **FLAMMABILITY & TRANSPORT INFORMATION**

Non-flammable

#### SAFETY INFORMATION AND PRECAUTION

- Do not apply at temperature below 10°c
- Provide adequate ventilation during use
- Keep out of reach of children
- Avoid contact with skin and eyes, wear suitable protective clothing such as overalls, goggles, dust masks and gloves
- Dispose in landfills only.